

# General Functions

## Retrieve WADL

This retrieves the WADL for the REST endpoint.

### URL

```
{{BaseURL}}/application.wadl  
  
OR  
  
{{BaseURL}}/application.wadl=detail=true
```

### Authorization

None. This is the only function which requires no authorization.

### Parameters

None

### Responses

If the request is performed, 200 OK is returned. See [Return Codes](#) for further possible status codes.

### Returned Data (200 OK)

The WADL for the REST API.

### Example

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>  
<application xmlns="http://wadl.dev.java.net/2009/02">  
  <doc xmlns:jersey="http://jersey.java.net/" jersey:generatedBy="Jersey: 2.30.1 2020-02-21 08:10:47"/>  
  <doc xmlns:jersey="http://jersey.java.net/" jersey:hint="This is simplified WADL with user and core resources only. To get full WADL with extended resources  
use the query parameter detail. Link: http://localhost:8091/rest/v1.0/application.wadl?detail=true"/>  
  <grammars/>  
  <resources base="http://localhost:8091/rest/v1.0/">  
    <resource path="{clientsID}/dialler/campaigns">  
      <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="clientsID" style="template" type="xs:int"/>  
      <method id="diallerCampaignsGetList" name="GET">
```

```
<response>
  <representation mediaType="application/json"/>
</response>
</method>
<resource path="campaign/{id}/resultCodes">
  <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="clientsID" style="template" type="xs:int"/>
  <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="id" style="template" type="xs:int"/>
  <method id="diallerCampaignsGetResultCodesByID" name="GET">
    <request>
      <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="languagesID" style="query" type="xs:int"/>
    </request>
    <response>
      <representation mediaType="application/json"/>
    </response>
  </method>
</resource>
<resource path="clone">
  <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="clientsID" style="template" type="xs:int"/>
  <method id="diallerCampaignsClone" name="POST">
    <request>
      <representation mediaType="application/json"/>
    </request>
    <response>
      <representation mediaType="application/json"/>
    </response>
  </method>
</resource>
<resource path="campaign">
  <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="clientsID" style="template" type="xs:int"/>
  <method id="diallerCampaignsGetByName" name="GET">
    <request>
      <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="name" style="query" type="xs:string"/>
    </request>
    <response>
      <representation mediaType="application/json"/>
    </response>
  </method>
  <method id="diallerCampaignsDeleteByName" name="DELETE">
    <request>
      <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="name" style="query" type="xs:string"/>
    </request>
    <response>
      <representation mediaType="application/json"/>
    </response>
  </method>
</resource>
<resource path="campaign/{id}">
  <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="clientsID" style="template" type="xs:int"/>
  <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="id" style="template" type="xs:int"/>
  <method id="diallerCampaignsDeleteByID" name="DELETE">
    <response>
```

```

        <representation mediaType="application/json"/>
    </response>
</method>
<method id="diallerCampaignsGetByID" name="GET">
    <response>
        <representation mediaType="application/json"/>
    </response>
</method>
</resource>
<resource path="routingrunner">
    <resource path="/run/{clientsID}/{caller}/{called}">
        <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="clientsID" style="template" type="xs:int"/>
        <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="caller" style="template" type="xs:string"/>
        <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="called" style="template" type="xs:string"/>
        <method id="runRoutingApplication" name="GET">
            <response>
                <representation mediaType="application/json"/>
            </response>
        </method>
    </resource>
</resource>
<resource path="{clientsID}/dialler/contacts">
    <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="clientsID" style="template" type="xs:int"/>
    <method id="getDiallerContacts" name="GET">
        <response>
            <representation mediaType="application/json"/>
        </response>
    </method>
    <resource path="import">
        <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="clientsID" style="template" type="xs:int"/>
        <method id="diallerContactsImport" name="POST">
            <request>
                <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="overwriteDuplicates" style="query" type="xs:boolean"/>
                <representation mediaType="application/json"/>
            </request>
            <response>
                <representation mediaType="application/json"/>
            </response>
        </method>
    </resource>
    <resource path="contact/{id}/unlock">
        <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="clientsID" style="template" type="xs:int"/>
        <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="id" style="template" type="xs:int"/>
        <method id="unlockDiallerContactsByID" name="PATCH">
            <response>
                <representation mediaType="application/json"/>
            </response>
        </method>
    </resource>
</resource path="contact">

```

```
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="clientsID" style="template" type="xs:int"/>
<method id="getDiallerContactsByUserData" name="GET">
  <request>
    <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="userData" style="query" type="xs:string"/>
  </request>
  <response>
    <representation mediaType="application/json"/>
  </response>
</method>
<method id="deleteDiallerContactsByUserData" name="DELETE">
  <request>
    <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="userData" style="query" type="xs:string"/>
  </request>
  <response>
    <representation mediaType="application/json"/>
  </response>
</method>
</resource>
<resource path="contact/lock">
  <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="clientsID" style="template" type="xs:int"/>
  <method id="lockDiallerContactsByUserData" name="PATCH">
    <request>
      <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="userData" style="query" type="xs:string"/>
    </request>
    <response>
      <representation mediaType="application/json"/>
    </response>
  </method>
</resource>
<resource path="contact/unlock">
  <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="clientsID" style="template" type="xs:int"/>
  <method id="unlockDiallerContactsByUserData" name="PATCH">
    <request>
      <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="userData" style="query" type="xs:string"/>
    </request>
    <response>
      <representation mediaType="application/json"/>
    </response>
  </method>
</resource>
<resource path="contact/{id}/lock">
  <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="clientsID" style="template" type="xs:int"/>
  <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="id" style="template" type="xs:int"/>
  <method id="lockDiallerContactsByID" name="PATCH">
    <response>
      <representation mediaType="application/json"/>
    </response>
  </method>
</resource>
<resource path="contact/{id}">
  <param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="clientsID" style="template" type="xs:int"/>
```

```
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="id" style="template" type="xs:int"/>
<method id="getDiallerContactsByID" name="GET">
  <response>
    <representation mediaType="application/json"/>
  </response>
</method>
<method id="deleteDiallerContactsByID" name="DELETE">
  <response>
    <representation mediaType="application/json"/>
  </response>
</method>
</resource>
</resource>
</resources>
</application>
```