

Value Reference - Action Codes

Purpose

The purpose of action codes are to define why an incoming call was not processed by the system.

Values

The following values are defined:

Value	Meaning
SRN_NOTAVAIL	The service number status was set to an inactive status.
SRN_NOTACTIVE	The service number was set to inactive.
MOBILE_NOTALLOW	Calls from mobile numbers are not allowed to this service number (settings additional checks in the service number).
INTERNAT_NOTALLOW	Calls from international numbers are not allowed to this service number (settings additional checks in the service number).
PAYPHONE_NOTALLOW	Calls from payphones are not allowed to this service number (settings additional checks in the service number).
CALLER_CLIENT_NOT_WHITELIST	The caller is not in the client whitelist for this number and a whitelist was configured.
CALLER_CLIENT_BLACKLIST	The caller is in the client blacklist for this number and a blacklist was configured.
CALLER_SRN_BLACKLIST	The caller is in the service number blacklist for this number and a blacklist was configured.
SRN_NO_APPLICATION	No application is associated with the service number.
SRN_NO_ACTIVE_APPLICATION	No <i>active</i> application is associated with the service number.
CALLER_GLOBAL_BLACKLIST	The caller is in the global blacklist for the system.
SRN_NOT_FOUND	Sending complete was sent in the signalling protocol and a service number was not found.
MORE_DIGITS	Sending complete was not sent in the signalling protocol and the sytem waited for more digits.