

Value Reference - Languages

Purpose

The LanguagesID values are used to identify a language to apply to a configuration or call flow in the jtel system, or record the actual language referenced during a call or event.

Values

Currently, the following values are defined. As this list may be expanded over future releases, it is a good idea to check the actual contents of the table for new values as they may be more current than this WIKI.

ID	Name	ISO Code	ISO Code (short)
1	English (United Kingdom)	en-GB	en
2	German (Germany)	de-DE	de
3	French (France)	fr-FR	fr
4	Spanish (Spain)	es-SP	es
5	Italian (Italy)	it-IT	it
6	Turkish (Turkey)	tr-TR	tr
7	English (United States)	en-US	en
8	Greek (Greece)	el-GR	el
9	Bosnian (Bosnia and Herzegovina)	bs-BA	bs
10	Bulgarian (Bulgaria)	bg-BG	bg
11	Hebrew (Israel)	he-IL	he
12	Croatian (Croatia)	hr-HR	hr
13	Macedonian (Macedonia)	mk-MK	mk
14	Polish (Poland)	pl-PL	pl
15	Romanian (Romania)	ro-RO	ro
16	Russian (Russia)	ru-RU	ru
17	Serbian (Serbia)	sr-CS	sr
18	Slovak (Slovakia)	sk-SK	sk
19	Slovenian (Slovenia)	sl-SI	sl
20	Czech (Czech Republic)	cs-CZ	cs
21	Hungarian (Hungary)	hu-HU	hu
22	Swedish (Sweden)	sv-SE	sv
23	Finnish (Finland)	fi-FI	fi
24	Norwegian Bokmål (Norway)	nb-NO	nb

26	Portuguese (Portugal)	pt-PT	pt
27	Ukrainian (Ukraine)	uk-UA	uk
28	Dutch (Netherlands)	nl-NL	nl
29	Danish (Denmark)	da-DK	da
30	Latvian (Latvia)	lv-LV	lv