

# ACD-G-002 - ACD Groups Report 3 and variants

[ 1 [Description](#) ] [ 1.1 [Service Level Calculation](#) ] [ 2 [Sample Execution \(Input\) Sample Report \(Output\)](#) ] [ 3 [Columns](#) ] [ 3.1 [Legend](#) ] [ 3.2 [Calls - Offered](#) ] [ 3.3 [Calls - In Service](#) ] [ 3.4 [Calls - Not In Service](#) ] [ 3.5 [Calls - Hungup <=](#) ] [ 3.6 [Calls - Hungup >](#) ] [ 3.7 [Calls - Number of Call Backs](#) ] [ 3.8 [Calls - Error](#) ] [ 3.9 [Calls - Queue Closed](#) ] [ 3.10 [Calls - Queue Full](#) ] [ 3.11 [Calls - Queue Timeout](#) ] [ 3.12 [Calls - Busy](#) ] [ 3.13 [Calls - Availability](#) ] [ 3.14 [Calls - Service Level](#) ] [ 3.15 [Answer Time - Ø Duration and Max. Duration](#) ] [ 3.16 [Hang Up Time - Ø Duration and Max. Duration](#) ] [ 3.17 [Talk Time - Ø Duration and Max. Duration](#) ] [ 3.18 [Post Call Time - Ø Duration and Max. Duration](#) ]

## Description

This report contains aggregated data for incoming calls to the selected ACD groups over the time period and granularity chosen. Data is aggregated over the selected ACD groups, and not presented individually per group.

**CAUTION**: if an incoming call is transferred from one ACD group to another, then this will be counted in BOTH ACD groups. This report is designed to be viewed by the manager / supervisor of the ACD groups in question, so aggregated data should be viewed with caution.

**P. S.** ACD-G-002-02, instead of containing the data of all selected ACD-Groups in one table, consist of one table per selected ACD-Group. The tables contain the same fields and are listed horizontally.

**P. S.** ACD-G-002-03 have an additional column "Line" containing the name of the Acd group.

## Service Level Calculation

The service level calculation in this report considers:

- Calls answered by agents within "ServiceLevelSeconds" measured from the time call entered the groups
- All calls which were offered to the groups

## Sample Execution (Input) Sample Report (Output)

## Columns

The following columns are provided.

## Legend

Table	Alias
StatisticsPartA (See also <a href="#">Table Reference - StatisticsPartA (A)</a> )	a
AcdStatisticsPartB (See also <a href="#">Table Reference - AcdStatisticsPartB (AcdB)</a> )	acdb
StatisticsPartB (See also <a href="#">Table Reference - StatisticsPartB (B)</a> )	b
AcdStatisticsLogin (See also <a href="#">Table Reference - AcdStatisticsLogin</a> )	login

## Calls - Offered

## Acdb - AcdbGetGroupCalls\_GroupServiceNumber

Criteria Used (see also <a href="#">ACD Group Service Number KPIs</a> )	Description
bOutbound = 0	All inbound calls which entered an ACD group and service number within a particular time slice.

## Calls - In Service

### Acdb - AcdbGetInServiceCallsByParam\_GroupServiceNumber

Criteria Used (see also <a href="#">ACD Group Service Number KPIs</a> )	Description
bOutbound = 0	All inbound calls which entered an ACD group and service number within a particular time slice, which were connected to an agent within (less than or equal to) the specified ServiceLevelSeconds.
( dtAgentConnect - dtGroupStart ) <= ServiceLevelSeconds	If ServiceLevelSeconds is 0, then this value is set to all calls connected to agents (i.e. ServiceLevelSeconds is ignored).

## Calls - Not In Service

### Acdb - AcdbGetNotInServiceCallsByParam\_GroupServiceNumber

Criteria Used (see also <a href="#">ACD Group Service Number KPIs</a> )	Description
dtAgentConnect IS NOT NULL	All inbound calls which entered an ACD group and service number within a particular time slice, which were connected to an agent outside of the specified ServiceLevelSeconds.
( acdb.dtAgentConnect - acdb.dtGroupStart ) > ServiceLevelSeconds	If ServiceLevelSeconds is 0, then this value is 0.

## Calls - Hungup <=

### Acdb - AcdbGetInTimeHangupCallsByParam\_GroupServiceNumber

Criteria Used (see also <a href="#">ACD Group Service Number KPIs</a> )	Description
---	-------------

bOutbound = 0 bCallerHangup = 1 dtAgentConnect IS NULL AcdGroupEndReasonsID IN ( 1, 2, 3, 4 ) ( dtGroupEnd - dtGroupStart ) <= HangupSeconds	All inbound calls which entered an ACD group and service number within a particular time slice, which were not connected to an agent and where the caller hungup before or in the ACD queue within the specified HangupSeconds.  See also <a href="#">Value Reference - AcdGroupEndReasons</a> .
--	--

## Calls - Hungup >

### AcdB - AcdGetNotInTimeHangupCallsByParam\_GroupServiceNumber

Criteria Used (see also <a href="#">ACD Group Service Number KPIs</a> )	Description
bOutbound = 0 bCallerHangup = 1 dtAgentConnect IS NULL AcdGroupEndReasonsID IN ( 1, 2, 3, 4 ) ( dtGroupEnd - dtGroupStart ) > HangupSeconds	All inbound calls which entered an ACD group and service number within a particular time slice, which were not connected to an agent and where the caller hungup before or in the ACD queue after the sepecified HangupSeconds.  See also <a href="#">Value Reference - AcdGroupEndReasons</a> .

## Calls - Number of Call Backs

Criteria Used (see also <a href="#">ACD Group Service Number KPIs</a> )	Description
bOutbound = 0 AcdGroupEndReasonsID = 109 bCallbackVoiceMailBooked = 1	All inbound calls which entered an ACD group and service number within a particular time slice, which were not connected to an agent and where the caller decided to leave the queue by pressing a DTMF and subsequently booked a callback or left a voice mail (which would have been initiated by an associated rule in the ACD group).  See also <a href="#">Value Reference - AcdGroupActionTypes</a>

## Calls - Error

<b>This column is the result of the following calculation:</b>
OfferedCalls - InServiceCalls - NotInServiceCalls - CallerHangupCallsInTime - CallerHangupCallsOutTime - QueueClosedCalls - QueueFullCalls - QueueTimeoutCalls - QueueLeaveDtmfCalls - BusyCalls

## Calls - Queue Closed

### AcdB - AcdGetQueueClosedCallsByGroupEndReason\_GroupServiceNumber

Criteria Used (see also <a href="#">ACD Group Service Number KPIs</a> )	Description
bOutbound = 0  AcdGroupEndReasonsID IN (100, 101, 102, 107, 108)  dtAgentConnect IS NULL	All inbound calls which entered an ACD group and service number within a particular time slice, which were not connected to an agent and where the call was handled by a rule at one of the specified AcdGroupEndReasons:  Group Start, Routing Application, Queue, Queue No Agents, Queue All Tried.  See also <a href="#">Value Reference - AcdGroupEndReasons</a> .

## Calls - Queue Full

### AcdB - AcdGetQueueFullCallsByGroupEndReason\_GroupServiceNumber

Criteria Used (see also <a href="#">ACD Group Service Number KPIs</a> )	Description
bOutbound = 0  AcdGroupEndReasonsID IN (105, 205)  dtAgentConnect IS NULL	All inbound calls which entered an ACD group and service number within a particular time slice, which were not connected to an agent and where the call could not enter the queue because the queue was full.  See also <a href="#">Value Reference - AcdGroupEndReasons</a> .

## Calls - Queue Timeout

### AcdB - AcdGetQueueTimeoutCallsByGroupEndReason\_GroupServiceNumber

Criteria Used (see also <a href="#">ACD Group Service Number KPIs</a> )	Description
bOutbound = 0  AcdGroupEndReasonsID IN (106, 206)  dtAgentConnect IS NULL	All inbound calls which entered an ACD group and service number within a particular time slice, which were not connected to an agent and where the call left the queue because the configured queue timeout was reached.  See also <a href="#">Value Reference - AcdGroupEndReasons</a> .

## Calls - Busy

### AcdB - AcdGetSystemHangupCallsByGroupEndReason\_GroupServiceNumber

Criteria Used (see also <a href="#">ACD Group Service Number KPIs</a> )	Description
bOutbound = 0 bCallerHangup = 0 AcdGroupEndReasonsID IN (1, 2, 3, 4, 207) dtAgentConnect IS NULL	All inbound calls which entered an ACD group and service number within a particular time slice, which were not connected to an agent and where the system hungup the call when executing a defined group rule or when there was no rule however one would have been required to continue processing.  See also <a href="#">Value Reference - AcdGroupEndReasons</a> .

## Calls - Availability

<b>This column is the result of the following calculation:</b>
$(\text{In Service} + \text{Not In Service}) * 100.0 / \text{Offered}$

## Calls - Service Level

<b>This column is the result of the following calculation:</b>
$\text{In Service} * 100.0 / \text{Offered}$

## Answer Time - Ø Duration and Max. Duration

The average and maximum duration of the following KPI:

Acdb - AcdGetAnswerDuration\_GroupServiceNumber

Criteria Used (see also <a href="#">ACD Group Service Number KPIs</a> )	Description
acdb.bOutbound = 0 acdb.dtAgentConnect IS NOT NULL SUM (acdb.dtAgentConnect - acdb.dtGroupStart)	The total talking time duration between a caller and an agent or a destination in the selected ACD groups and via the selected service numbers within a particular time slice.

## Hang Up Time - Ø Duration and Max. Duration

The average and maximum duration of the following KPI:

**Acdb - AcdGetCallerHangupCallsDuration\_GroupServiceNumber**

Criteria Used (see also <a href="#">ACD Group Service Number KPIs</a> )	Description
bOutbound = 0 dtAgentConnect IS NULL bCallerHangup = 1 AcdGroupEndReasonsID IN ( 1, 2, 3, 4 )	The time difference between dtGroupStart and dtGroupEndfor calls where the caller did not speak to an agent and hung up before or whilst in the ACD queue.  See also <a href="#">Value Reference - AcdGroupEndReasons</a> .

## Talk Time - Ø Duration and Max. Duration

The average and maximum duration of the following KPI:

### AcdB - AcdGetCallDuration\_GroupServiceNumber

This KPI references all data from the StatisticsPartB table (agent calls) for each found entry in the AcdStatisticsPartB table. This enables the times agents were actually connected with callers to be measured.

Criteria Used (see also <a href="#">ACD Group Service Number KPIs</a> )	Description
bOutbound = 0 b.CONNRES = 1 b.dtCallConnect IS NOT NULL b.UsersID IS NOT NULL	The time difference between b.dtCallConnect or b.dtWhisperEnd (whichever is not NULL and later) and b.dtCallEndfor calls answered by agents (UsersID NOT NULL).

## Post Call Time - Ø Duration and Max. Duration

The average and maximum duration of the following KPI:

### AcdB - AcdGetPostCallDuration\_GroupServiceNumber

Criteria Used (see also <a href="#">ACD Group Service Number KPIs</a> )	Description
bOutbound = 0 b.CONNRES = 1 b.PostCallInterval > 0	The PostCallInterval from StatisticsPartB for all calls connected to agents for which post call work was performed (PostCallInterval > 0).  See also <a href="#">Value Reference - CONNRES</a> .

[ 1 Description ][ 1.1 Service Level Calculation ][ 2 Sample Execution (Input) Sample Report (Output) ][ 3 Columns ][ 3.1 Legend ][ 3.2 Calls - Offered ][ 3.3 Calls - In Service ][ 3.4 Calls - Not In Service ][ 3.5 Calls - Hungup <= ][ 3.6 Calls - Hungup > ][ 3.7 Calls - Number of Call Backs ][ 3.8 Calls - Error ][ 3.9 Calls - Queue Closed ][ 3.10 Calls - Queue Full ][ 3.11 Calls - Queue Timeout ][ 3.12 Calls - Busy ][ 3.13 Calls - Availability ][ 3.14 Calls - Service Level ][ 3.15 Answer Time - Ø Duration and Max. Duration ][ 3.16 Hang Up Time - Ø Duration and Max. Duration ][ 3.17 Talk Time - Ø Duration and Max. Duration ][ 3.18 Post Call Time - Ø Duration and Max. Duration ]